



Spartan UK Ltd

Declaration of Performance

(according to Annex III of EU Regulation No. 305/2011 and ammended per EU Regulation No. 574/2014)

DOP/2019/S460N

Unique identification code of the product - type:
DOP/2019/S460N

Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification:

Hot - rolled steel plates from structural steels accordant to the regulations of EN10025-2,-3,-5

Name, registered trade name or registered trade mark and contact address of the manufacturer:

Spartan UK Ltd
Ropery Road, Teams, Gateshead, Tyne and Wear, NE8 2RD, United Kingdom
Tel. : +44 (0) 191 4604245
E-mail: gary.robinson@spartanuk.co.uk

Name and representative whose mandate covers the tasks specified in Article 12 (2):

Not Applicable

System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in Annex V to Regulation (EU) No. 305/2011:

System 2+

In case of the declaration of performance concerning a construction product covered by a harmonized standard:

Hot rolled plates from structural steels with strength level S235 up to S460 according to EN 10025-1:2004
Notified factory production control certification body TUV NORD Systems GmbH & Co.
KG No. 0045
Große Bahnstraße 31
D-22525 Hamburg
Germany
Certificate No: 0045-CPR-0950 dated 15/10/2020

The performance of the product identified in points 1 and 2 is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identify above

Signed for and on behalf of the manufacturer by:
Gary Robinson, Quality Manager

Gateshead, 20th of October 2020

Essential Characteristic	Declared Performance		Harmonised Standard											
	Nominal thickness (mm)	Values (MPa) Min												
Yield Strength	≤ 16	460	EN 10025-1 (2004)											
	> 16 ≤ 40	440												
	> 40 ≤ 63	430												
	> 63 ≤ 80	410												
	> 80 ≤ 100	400												
	> 100 ≤ 150	380												
	> 150 ≤ 200	370												
Tensile Strength	≤ 100	540 to 720	EN 10025-1 (2004)											
	> 100 ≤ 200	530 to 710												
	> 200 ≤ 250	-												
Elongation	≤ 40	17	EN 10025-1 (2004)											
	> 40 ≤ 63	17												
	> 63 ≤ 80	17												
	> 80 ≤ 200	17												
	> 200 ≤ 250	-												
Impact strength for longitudinal test specimens KV	Test temperature (°C)	Min Values (J)	EN 10025-1 (2004)											
	20	55												
	0	47												
	-10	43												
	-20	40												
	-30	-												
	-40	-												
-50	-													
Chemical composition of the ladle analysis:														
	C % max.	Si % max.	Mn %	P % max.	S % max.	Nb % max.	V % max.	Al _{total} % min.	Ti % max.	Cr % max.	Ni % max.	Mo % max.	Cu % max.	N % max.
S460N	0.20	0.60	1.00-1.70	0.030	0.025	0.05	0.20	0.02	0.05	0.30	0.80	0.10	0.55	0.025
Maximum CEV based on ladle analysis														
Maximum CEV in % for nominal product thickness in mm														
	≤ 63	> 63 ≤ 100	> 100 ≤ 250											
S460N	0.53	0.54	0.55											



0045

Spartan UK Ltd, Ropery Road, Gateshead, Tyne and Wear, NE8 2RD Great Britain

O6

0045-CPR-0950

DOP No: DOP/2019/S460N

EN10025-1:2004

Hot rolled plates from structural steels of Grade S460N / 1.8901 according to EN10025-3:2019

Intended uses:

Building constructions or civil engineering in accordance with EN1090 when supplied with 3.1 certification to EN10204 containing product identification details.

Information on regulated characteristics in accordance with EN10025-3 for:

Tensile Strength:

Yield Strength:

Elongation:

Impact Strength:

Weldability:

Regulated substance: No performance determined