

Declaration of Performance

Spartan UK Ltd

Declaration of Performance

(According to Annex III of EU Regulation No. 305/2011 and amended per EU Regulation No. 574/2014)

CEDOP/2018/S275J2

1. Unique identification code of the product-type:

CEDOP/2018/S275J2

2. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification:

Hot-rolled rolled products of structural steels

3. Name, registered trade name or registered trademark and contact address of the manufacturer:

Spartan UK Ltd Ropery Road, Teams, Gateshead, Tyne and Wear, NE8 2RD, United Kingdom Tel: +44 (0) 191 4604245 E-mail: gary.robinson@spartanuk.co.uk

4. Name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12 (2):

Not applicable

5 System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in Annex V to Regulation (EU) No. 305/2011:

System 2+

6 In case of the declaration of performance concerning a construction product covered by a harmonized standard:

Hot-rolled rolled products of structural steels according to EN 10025-1:2004

Notified factory production control certification body TUV NORD Systems Gmbh & Co. KG No. 0045

Große Bahnstraße 31

D-22525 Hamburg

Germany

Certificate No: 0045-CPR-0950



Declaration of Performance

7 Declared performance

Essential Characteristic	Peri	Harmonised Standard	Technical Specification		
	Nominal thickness (mm)	Values (MPa) Min		EN10025-2	
	≤ 16	275			
	> 16 ≤ 40	265			
Yield Strength	> 40 ≤ 63	255			
rield Strength	> 63 ≤ 80	245			
	> 80 ≤ 100	235			
	> 100 ≤ 150	225			
	> 150 ≤ 200	215			
	> 200 ≤ 250	205			
Tensile Strength	Nominal thickness (mm)	Values (MPa)			
	≥ 3 ≤ 100	410 to 560	EN 10025-1		
	> 100 ≤ 150	400 to 540	EN 10025-1		
	> 150 ≤ 250	380 to 540			
Elongation	Nominal thickness (mm)	Values (%) Min			
	> 3 ≤ 40	21			
	> 40 ≤ 63	20			
	> 63 ≤ 100	19			
	> 100 ≤ 150	19			
	> 150 ≤ 250	18			
Impact strength for longitudinal test specimens KV at -20°C	Nominal thickness (mm)	Values (J)			
	≤ 150	min 27			
	> 150 ≤ 250	min 27			

Chemical composition of the ladle analysis

	C in % max. for nominal product thickness in mm		Si %	Mn % max.	P % max.	S % max.	N % max.	Cu %	Other % max.	
	≤16	> 16 ≤ 40	>40	max.	max.	max.	max.	max.	max.	70 IIIa X.
S275J2	0.18	0.18	0.18	-	1.50	0.025	0.025	-	0.55	-

Maximum CEV based on the ladle analysis

	Maximum CEV in % for nominal product thickness in					
	mm					
	≤30	> 30 ≤ 40	>40 ≤150	>150 ≤ 250		
S275J2	0.40	0.40	0.42	0.44		



Declaration of Performance

Spartan UK

8 The performance of the product identified in points 1 and 2 is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above

Signed for and on behalf of the manufacturer by:

Gary Robinson, Quality Manager

Gateshead, 22nd September 2022