

### **Declaration of Performance**

**Spartan UK Ltd** 

#### **Declaration of Performance**

(According to Annex III of EU Regulation No. 305/2011 and amended per EU Regulation No. 574/2014)

DOP/2018/S235J2W

1. Unique identification code of the product-type:

#### DOP/2018/S235J2W

2. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification:

Hot-rolled plates from structural steels accordant to the regulations of EN10025-2, -3, -5

3. Name, registered trade name or registered trade mark and contact address of the manufacturer:

# Spartan UK Ltd Ropery Road, Teams, Gateshead, Tyne and Wear, NE8 2RD, United Kingdom Tel.: +44 (0) 191 4604245 E-mail: gary.robinson@spartanuk.co.uk

4. Name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12 (2):

#### Not applicable

5 System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in Annex V to Regulation (EU) No. 305/2011:

#### System 2+

6 In case of the declaration of performance concerning a construction product covered by a harmonized standard:

Hot rolled plates from structural steels with strength level S235 up to S460 according to DIN EN 10025-2,-3,-5 Notified factory production control certification body TUV NORD Systems Gmbh & Co. KG No. 0045 Große Bahnstraße 31

> D-22525 Hamburg Germany

Certificate No: 0045-CPR-0950 dated 01.09.2015



# **Declaration of Performance**

# Spartan UK

## 7 Declared performance

Essential Characteristic	Peri	Harmonised Technical Specification			
	Nominal thickness (mm)	Values (MPa) Min			
Yield Strength	≤ 16	235			
	> 16 ≤ 40	225			
	> 40 ≤ 63	215			
	> 63 ≤ 80	215			
	> 80 ≤ 100	215			
	> 100 ≤ 150	195			
Tensile Strength	Nominal thickness (mm)	Values (MPa)			
rensile strength	≥ 3 ≤ 100	360 to 510	EN 10025-5 (2004)		
	> 100 ≤ 150	350 to 500			
	Nominal thickness (mm)	Values (%) Min			
Elongation	> 3 ≤ 40	24			
	> 40 ≤ 63	23			
	> 63 ≤ 100	22			
	> 100 ≤ 150 22				
Impact strength for longitudinal test	Test Temperature (°C)	Values (J)			
specimens KV	- 20 min 27				

# Chemical composition of the ladle analysis

	C % max.	Si % max.	Mn %	Р %	S % max.	N % max.	Addition of nitrogen binding elements	Cr %	Cu %
S235J2W	0.13	0.40	0.20 - 0.60	max. 0.035	0.030	-	yes	0.40 - 0.80	0.25 - 0.55



## **Declaration of Performance**

# Spartan UK

The performance of the product identified in points 1 and 2 is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identify above

Signed for and on behalf of the manufacturer by:

Gary Robinson, Quality Manager

Gateshead, 15<sup>th</sup> of March 2018